

# **Wifi Smart Plug** enjoy more convenient and intelligent life



## Product highlights:

Voice control  
 Remote control from anywhere at anytime  
 Overcurrent protection and inbuilt surge  
 Set schedules and countdown  
 Real-time display of energy monitoring.  
 Works with Amazon Alexa and Google Home



| Product Name            |                     | Smart Wi-Fi Plug Mini 2 in 1                                                                                                                                                                        | Model no            | NX-SP201                                                                                                                                                                                                   |
|-------------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| External feature        | AC input jack(pcs)  | 2                                                                                                                                                                                                   | Button(pcs)         | 2                                                                                                                                                                                                          |
|                         | Indicator light     | 2 Red lights and 2 blue lights                                                                                                                                                                      | Product Size(mm)    | 119*40*51                                                                                                                                                                                                  |
| Technical specification | Input Voltage       | 50Hz/60Hz AC100~240V                                                                                                                                                                                | Output Voltage      | 50Hz/60Hz AC100~240V                                                                                                                                                                                       |
|                         | Input Current       | 15A                                                                                                                                                                                                 | Output Current      | 15A                                                                                                                                                                                                        |
|                         | Shell Material      | Flame retarding V0 class ABS+PC                                                                                                                                                                     | Plug Standard       | US standard                                                                                                                                                                                                |
|                         | Storage temperature | -20℃~70℃ RH≤80%                                                                                                                                                                                     | Working temperature | 0℃~40℃ RH≤80%                                                                                                                                                                                              |
|                         | Radio Technology    | IEEE 802.11B/G/N                                                                                                                                                                                    | Wireless Type       | WiFi 2.4G 1T1R                                                                                                                                                                                             |
|                         | Certified           | ETL,CE,RoHS                                                                                                                                                                                         | Compatible          | Amazon Alexa, Google Home, IFTTT                                                                                                                                                                           |
| Function                | Timer               | 1. Timed on/off<br>2. Time setting: time (0~23H), minute (0~59Min)<br>3. Name customization (default: On/Off Schedule)<br>4. Support for adding 32                                                  | Delayer             | 1. Countdown (time) off/on;<br>2. Time setting: time (0~23H), minute (1~59min)                                                                                                                             |
|                         | Device Sharing      | A, the main account:<br>1. Share access to other users;<br>2. Manage sub accounts<br>B, the sub account:<br>1. After obtaining the permission, you can switch, set the timing and the delay switch; | Energy monitoring   | 1. Calculate the electrical quantity by day/week/month/year;<br>2. The electrical consumption is graphically displayed by day/week/month/year;<br>3. Real-time display of voltage, current, and power data |
|                         | Overload protection | Pass 1.0 times current (15A), the product should work normally within 1 hour; 1875W 15.5A 30S automatically close the output.                                                                       | App support         | ISO 8.0 or Android 4.1 and higher                                                                                                                                                                          |

## Packaging

| Inner box |              |         |         | Outer carton |              |          |          | 20' container |         |
|-----------|--------------|---------|---------|--------------|--------------|----------|----------|---------------|---------|
| Qty (pcs) | size (cm)    | N.W (g) | G.W (g) | Qty (pcs)    | Size (cm)    | N.W (kg) | G.W (kg) | Qty (pcs)     | Cartons |
| 1 pc      | 12.1*4.2*5.5 | 109     | 130     | 120          | 50.3*35*23.7 | 13.08    | 16.17    | 79200         | 660     |